


Product	Sinopec Classic Antiwear Hydraulic Oil L-HM
Summary	<p>Product description</p> <p>Sinopec Classic Antiwear Hydraulic Oil L-HM is a line of premium quality antiwear lubricants blended using selected and carefully refined high-quality mineral oils, combined with a multifunctional additive system and available in a wide viscosity range from ISO Grade 32 to 100. This line of oil products is applicable to medium-pressure hydraulic system of industrial and marine equipment as well as in mobile machinery.</p>


Available sizes



PAIL – 18L



DRUM – 200L



IBC – 1000L

Also
available
in bulk

Applications

Sinopec Classic Antiwear Hydraulic Oil L-HM is suitable for use in:

- Hydraulic applications in a wide variety of industrial, marine and mobile equipment.
- Vane and gear pumps operating under medium loads.

Features and benefits

- High-quality base oils combined with multifunctional additive technology provide good antiwear properties, rust protection, good demulsibility, oxidation resistance, good antifoam properties and fast air release properties, to protect and extend the life of hydraulic pumps and systems.
- Good hydrolytic stability and filterability, ensure optimum product life and performance, and prevent filter blocking.
- Fully compatible with common seal materials usually found in hydraulic systems, to extend seal life and prevent fluid leakage.

Product Data Sheet

Typical data

Sinopec Classic Antiwear Hydraulic Oil L-HM				
ISO viscosity grade	32	46	68	100
Kinematic viscosity, ASTM D 445				
cSt @ 40°C	32.98	45.22	68.63	100.4
cSt @ 100°C	5.43	6.49	8.38	11.00
Viscosity index, ASTM D 2270	98	91	90	93
Air release at 50°C, mins, ASTM D 3427	1.9	4.3	7.5	15
Foaming characteristics, sequences 1, 2 and 3, ASTM D 892	45/0 20/0 50/0	70/0 20/0 80/0	20/0 20/0 25/0	20/0 20/0 30/0
Neutralisation number, mg KOH/g, ASTM D 974	0.45	0.44	0.49	0.55
FZG test (A/8.3/90), fail load stage, DIN 51345	10	10	10	10
Rust prevention, ASTM D 665				
distilled water	pass	pass	pass	pass
Copper corrosion, 3 hours @ 100°C, ASTM D 130	1b	1b	1b	1b
Water separability, ASTM D 2711	16.5 (54°C)	17.9(54°C)	18(54°C)	20 (82°C)
Pour point, °C, ASTM D 97	-18	-15	-15	-13
Flash point (COC), °C, ASTM D 92	217	224	237	258

These data are given as an indication of typical values and not as exact specifications.

Industry and OEM specifications

Sinopec Classic Antiwear Hydraulic Oil L-HM meets the performance requirements of the following industry specifications:	
DIN	51524 Pt 2
GB ¹	11118.1 -2011(L-HM, Classic)
ISO	11158 (L-HM)

¹ Note: 'GB' standards are the National Standards of the People's Republic of China.

Product Data Sheet

Accuracy of information

Data provided in this PDS is typical and subject to change as a result of continuing product research and development. The information given was correct at the time of printing. The typical values given are subject to variations in the testing procedures and the manufacturing process may also result in slight variations. Sinopec guarantees that its lubricants meet any industry and OEM specifications referred to on this data sheet.

Sinopec cannot be held responsible for any deterioration in the product due to incorrect storage or handling. Information on best practice is available from your local distributor.

Product and environmental safety

This product should not cause any health problems when used in the applications suggested and when the guidance provided in the Material Safety Data Sheet (MSDS) is followed. Please consult the MSDS for more detailed advice on handling; MSDSs are available from your local distributor. Do not use the product in applications other than those suggested.

As with all products, please take care to avoid environmental contamination when disposing of this product. Used oil should be sent for reclamation/recycling or, if not possible, must be disposed of according to relevant government/authority regulations.

The SINOPEC trademark is registered and protected.

Issued: March 2017

© Sinopec 2017

Sinopec Classic Antiwear Hydraulic Oil L-HM